

20.50.020 Standards – Dimensional requirements.

A. Table 20.50.020(1) specifies densities and dimensional standards for permitted development applicable in residential zones.

Table 20.50.020(2) specifies densities and dimensional standards for residential development in other zones.

Table 20.50.020(1) – Densities and Dimensions in Residential Zones

Note: Exceptions to the numerical standards in this table are noted in parentheses and described below.

Residential Zones							
STANDARDS	R-4	R-6	R-8	R-12	R-18	R-24	R-48
Base Density: Dwelling Units/Acre	4 du/ac	6 du/ac (7)	8 du/ac	12 du/ac	18 du/ac	24 du/ac	48 du/ac
Min. Density	4 du/ac	4 du/ac	4 du/ac	6 du/ac	8 du/ac	10 du/ac	12 du/ac
Min. Lot Width (2)	50 ft	50 ft	50 ft	30 ft	30 ft	30 ft	30 ft
Min. Lot Area (2)	7,200 sq ft	7,200 sq ft	5,000 sq ft	2,500 sq ft	2,500 sq ft	2,500 sq ft	2,500 sq ft
Min. Front Yard Setback (2) (3)	20 ft	20 ft	10 ft	10 ft	10 ft	10 ft	10 ft
Min. Rear Yard Setback (2) (4) (5)	15 ft	15 ft	5 ft	5 ft	5 ft	5 ft	5 ft
Min. Side Yard Setback (2) (4) (5)	5 ft min. and 15 ft total sum of two	5 ft min. and 15 ft total sum of two	5 ft	5 ft	5 ft	5 ft	5 ft
Base Height (9)	30 ft (35 ft with pitched roof)	30 ft (35 ft with pitched roof)	35 ft	35 ft	35 ft (40 ft with pitched roof)	35 ft (40 ft with pitched roof)	35 ft (40 ft with pitched roof) (8)
Max. Building Coverage (2) (6)	35%	35%	45%	55%	60%	70%	70%
Max. Hardscape (2) (6)	45%	50%	65%	75%	85%	85%	90%

Exceptions to Table 20.50.020(1):

(1) Repealed by Ord. 462.

- (2) These standards may be modified to allow zero lot line developments. Setback variations apply to internal lot lines only. Overall site must comply with setbacks, building coverage and hardscape limitations; limitations for individual lots may be modified.
- (3) For exceptions to front yard setback requirements, please see SMC 20.50.070.
- (4) For exceptions to rear and side yard setbacks, please see SMC 20.50.080.
- (5) For developments consisting of three or more dwellings located on a single parcel, the building setback shall be 15 feet along any property line abutting R-4 or R-6 zones. Please see SMC 20.50.130.
- (6) The maximum building coverage shall be 35 percent and the maximum hardscape area shall be 50 percent for single-family detached development located in the R-12 zone.
- (7) The base density for single-family detached dwellings on a single lot that is less than 14,400 square feet shall be calculated using a whole number, without rounding up.
- (8) For development on R-48 lots abutting R-12, R-24, R-48, O, NB, CB, NCBD, MUZ, I, and CZ zoned lots the maximum height allowed is 50 feet and may be increased to a maximum of 60 feet with the approval of a conditional use permit.
- (9) Base height for high schools in all zoning districts except R-4 is 50 feet. Base height may be exceeded by gymnasiums to 55 feet and by theater fly spaces to 72 feet.